


## Technical data


Voltage	220-240 VAC 50/60 Hz
System effect	4.5W
Colour rendering	CRI>95
Expected lifespan	50,000 hours L70 B50
Dimmable, how	Yes, trailing edge
Flicker free	Yes, according to the new Ecodesign / ErP directive
SVM <0.4	Yes
PstLM <1	Yes
SDCM	≤3
Beam angle	36°
Cut out	Ø55 mm
Installation height	33 mm
Exterior dimension	Ø65 mm
Dimension driver	L: 50 mm, W: 50.2 mm, H: 22.5 mm
Dimension connector box	L: 62.5 mm, W: 44 mm, H: 26 mm
Tilt angle	20°
Possibility of through wiring - quantity	Yes, 2 x 3G1,5 mm <sup>2</sup> - 30 pcs.
Operating temperature	-20° - +45°
Storage temperature	-40° - +80°
IP rating, front / back	IP44 / IP20 (is intended for installation in areas 1 and 2)
Insulation class	Class II
Material	Aluminium, plastic
Approvals	CE

## Product information

- Approved for installation directly in the insulation and flammable materials
- For indoor and outdoor use
- The downlight can be driven either by a stand-alone driver or by Nordtronic's 25W driver (25W or up to 8 pcs. Ø55 mm downlight)
- Replaceable light source
- High colour rendering index – CRI>95
- Flicker free according to the new Ecodesign / ErP directive
- Intended for installation in areas 1 and 2
- Quick and easy mounting with springs
- Low installation height – 33 mm
- 3-pole leavers in the connector box
- Approved for through wiring – 2 x 3G1.5 mm<sup>2</sup> - 30 pcs.
- Possibility of mounting with cable or 16 mm flex tube
- 7 years product warranty
- Up to 10 years surface warranty



NB: Always use cables of a type approved for permanent installation according to the current legislation. If the cables are in contact with the lamp cover, use cables with an operating temperature of at least 70° C.



## Low Profile Flexible G2 Ø55 with driver | 2700K | 270lm

Item no.	EAN no.	Design, colour	Light source	Environment	Warranty, product / surface
35511012	5704629002647	○ matt white (RAL 9010)	3W LED, Item no. 98121552	indoor and outdoor	7 years / 10 years
35511092	5704629002708	○ matt black (RAL 9005)	3W LED, Item no. 98121552	indoor and outdoor	7 years / 10 years
35511022	5704629002678	○ brushed alu	3W LED, Item no. 98121552	indoor	7 years
35511522	5704629002739	○ brushed alu	3W LED, Item no. 98121552	outdoor	7 years

## Low Profile Flexible G2 Ø55 with driver | 3000K | 280lm

Item no.	EAN no.	Design, colour	Light source	Environment	Warranty, product / surface
35511013	5704629002654	○ matt white (RAL 9010)	3W LED, Item no. 98121553	indoor and outdoor	7 years / 10 years
35511093	5704629002715	○ matt black (RAL 9005)	3W LED, Item no. 98121553	indoor and outdoor	7 years / 10 years
35511023	5704629002685	○ brushed alu	3W LED, Item no. 98121553	indoor	7 years
35511523	5704629002746	○ brushed alu	3W LED, Item no. 98121553	outdoor	7 years

## Low Profile Flexible G2 Ø55 with driver | 4000K | 300lm

Item no.	EAN no.	Design, colour	Light source	Environment	Warranty, product / surface
35511014	5704629002661	○ matt white (RAL 9010)	3W LED, Item no. 98121554	indoor and outdoor	7 years / 10 years
35511094	5704629002722	○ matt black (RAL 9005)	3W LED, Item no. 98121554	indoor and outdoor	7 years / 10 years
35511024	5704629002692	○ brushed alu	3W LED, Item no. 98121554	indoor	7 years
35511524	5704629002753	○ brushed alu	3W LED, Item no. 98121554	outdoor	7 years