

**Zoe 12W**



**Technical data**

<b>Voltage</b>	220-240 VAC 50 Hz
<b>System effect</b>	12W
<b>Light source</b>	9W LED, item no. 96110023 <span style="border: 1px solid black; padding: 0 2px;">E</span>
<b>Colour temperature</b>	3000 / 4000 Kelvin CCT switch
<b>Light intensity</b>	850 / 900 Lumen
<b>Colour rendering</b>	CRI>90
<b>Expected lifespan</b>	50,000 hours
<b>Dimmable</b>	Yes, trailing edge
<b>Flicker free</b>	Yes, according to the new Ecodesign / ErP directive (September 2021)
<b>SVM &lt;0.4</b>	Yes
<b>PstLM &lt;1</b>	Yes
<b>SDCM</b>	One single LED <3, on complete fixture <6
<b>Beam angle</b>	110°
<b>Exterior dimensions</b>	Ø250 mm, D: 55 mm
<b>Possibility of through wiring</b>	Yes, 2 x 5G1,5
<b>IP-class</b>	IP65
<b>IK-class</b>	IK10
<b>Insulation class</b>	Class I
<b>Material</b>	Aluminium, polycarbonat
<b>Environment</b>	Indoors and outdoors
<b>Warranty</b>	5 years
<b>Approvals</b>	CE



\*The drawing is not drawn to scale

220-240 VAC	12W	LED	DRIVER	3000K / 4000K	850 / 900 Lumen	CRI>90
Beam angle	Eye icon	110°	50000	IP65	IK10	Through wiring
CE	RoHS	10	80	CE	RoHS	RoHS

**Product information**

- Modern luminaire made of aluminium and polycarbonat
- High lumen output
- Flicker free according to the new Ecodesign / ErP directive (September 2021)
- CCT switch 3000K / 4000K
- High colour rendering index (CRI>90)
- Dimmable (trailing edge)

NB: Always use cables of a type approved for permanent installation according to the current legislation.

<b>Item no.</b>	<b>EAN no.</b>	<b>Colour</b>
96111091	5704629001299	Black, RAL 9005