
Exit sign 3W

Technical data

| Voltage | 220-240 VAC 50 Hz | |
|-------------------------------|--------------------------------|--|
| System effect | 3W | |
| Light source | LED | |
| Colour temperature | 6000 Kelvin | |
| Light intensity | 40-60 Lumen | |
| Colour rendering | CRI>82 | |
| Beam angle | 160° | |
| Exterior dimensions | L: 310 mm, W: 35 mm, H: 230 mm | |
| Tilt angle | 90° | |
| Operating temperature | -5° - +45° | |
| Reading distance | Max. 24 m | |
| Battery | 3.6V 900mAh Ni-Cd accu | |
| Manual test button | Yes | |
| Possibility of through wiring | No | |
| IP-class | IP20 | |
| Insulation class | Class I | |
| Material | Polycarbonate, metal | |
| Environment | Indoors | |
| Warranty | 2 years | |
| Approvals | CE | |
| | | |





*The drawing is not drawn to scale



NB: Always use cables of a type approved for permanent installation according to the current legislation. If the cables are in contact with the lamp cover, use cables with an operating temperature of at least 70° C.

....

IP20

90

160

X

1

| Item no. | EAN no. | Colour |
|----------|---------------|--------|
| 97131026 | 5704629000315 | White |

Accessories

220-240

VAC

ЗW

10

 \checkmark

6000

Kelvin

200

Product information

3 hours of emergency operation
Reading distance: Max. 24 m
Incl. 3 x 2 pictograms

40-60

Lumen

CE

• Can be mounted directly on the wall and ceiling

Test the lighting and the battery periodically

• It is recommended to replace the battery every 4 years

CRI>82

RoHS

• In case of power failure, the built-in battery pack providesapprox.

| Item no. | EAN no. | Туре |
|----------|---------------|--------------------|
| 98911010 | 5704629000438 | Battery pack |
| 98912011 | 5704629000445 | Wall swing bracket |