

LED Driver - not dimmable, 2.5-14W 350mA


Technical data

Primary Voltage	220-240VAC
Secondary amperage	350mA
Min. load	2.5W
Max. load	14W
Efficiency	+60%
Dimmable	No
Fuse	Built-in thermal fuse with auto reset
Operating temperature	-10° / +40°
IP-class	IP20
Insulation class	Class II
Material	Plastic
Distribution box on secondary side	Yes, with 6 outputs
Cable from the secondary side	Yes, 14.5 cm to distribution box
Connection cable on primary side	Yes, 1 m cable equipped with switch and CE plug
Possibility of attachment	Yes, using two screws (not included)
Dimensions driver	L: 125 mm, W: 41 mm, H: 23 mm
Dimensions distribution box	L: 51 mm, W: 30 mm, H: 16 mm
Warranty	2 years
Approvals	CE



Product information

- LED driver for Linea spots, 6 outputs
- Flicker free according to the new Ecodesign / ErP directive (September 2021)
- Incl. 1 meter 230Vac wire equipped with switch and CE plug
- Do NOT plug in any LED lamps, when connected to power**



*The drawing is not drawn to scale

Item number	EAN no.	Variant
98514021	5704629001060	LED Driver - not dimmable, 2.5-14W 350mA