



Technical data

Primary voltage	220-240VAC 50/60 Hz
System effect	1-19W
Secondary amperage	350mA
Min. load	1W
Max. load	19W
Efficiency	+83%
Vout range	2-54 Vdc
Max. voltage (open circuit)	≤60 Vdc
Expected lifespan	50,000 hours
Dimmable	No
Flicker free	Yes, according to the new Ecodesign / ErP directive
Fuse	Built-in thermal fuse with auto reset
Distribution box on secondary side	Yes, with 6 outputs
Cable from the secondary side	Yes, 15 cm to distribution box
Connection cable on primary side	Yes, 2 m cable equipped with 2P plug
Possibility of attachment	Yes, using screws (not included)
Dimensions driver	L: 116 mm, W: 41 mm, H: 25 mm
Dimensions distribution box	L: 58 mm, B: 37 mm, H: 10 mm
Ambient temperature range t_a	-20° - +45°
Storage temperature range	-20° - +70°
Mains switching cycles	>100,000
Leakage current	0.45mA
IP rating	IP20
Insulation class	Class II, SELV
Material	Plastic
Environment	Indoor
Warranty	5 years
Approvals	CE

Product information

- LED driver for cabinet lighting and mini downlights (350mA, 6 outputs)
- Built-in thermofuse with auto reset
- Quick and easy installation
- Can be fastened by screws
- Do NOT plug in any LED lamps, when connected to power**



Max. LED driver per circuit breaker

Circuit breaker	B10	B13	B16	C10	C13	C16
Max. number	14	23	28	37	48	59

Item no.	EAN no.	Type
98514026	5704629004993	dimmable

NB: Always use cables of a type approved for permanent installation according to the current legislation. If the cables are in contact with the lamp cover, use cables with an operating temperature of at least 70° C.